

USB 2.0 4Port Hub User's Manual



USB 2.0 4Port Hub

PACKING LIST

- The USB 2.0 Hub
- USB Cable (A type to Mini B type 1.8 M)
- AC adapter(DC5V, 2.1A)
- This Manual.

※ This package contains each of products listed above.

Introduction:

This 4 Port USB2.0 hub is compliant with latest USB Spec Revision 2.0, i.e. support high-speed (480 Mbps), full-speed (12 Mbps) and low-speed (1.5 Mbps) data transaction rate. It is fully backward compatible with previous USB 1.1 products. You will enjoy the high-speed that USB2.0 technology provides, particularly when you are operating the devices, which need mass data transmission, such as DV Camcorder, Digital camera...etc.

Features:

- Compact design for easy use.
- Compliant with USB Specification Revision 2.0.
- All four type-A USB ports support high-speed (480 Mbps), full-speed (12 Mbps) and low-speed (1.5 Mbps) data transmission.
- A maximum of 127 devices can be supported.
- Support Self-powered mode only.

System Requirements:

- Use with IBM PC or Mac compatible with enabled USB ports (a USB 2.0 port and USB 2.0 drivers are required for USB 2.0 operation)
- Windows 98, 98SE, ME, 2000 Professional and Windows XP
- OS 9.1 or later, OS X 10.1or later
- USB 2.0 Drivers (for high speed USB 2.0)


CAUTION!

1. Computer must be USB2.0 compatible; otherwise it will be treated as USB1.1 Hub.
2. The USB 2.0 Hub must to be connected in AC Adapter.

■ **Remarks:**

- If your computer does not have built-in USB2.0 compatible port, we recommend connecting the USB 2.0 to USB 2.0 PCI Card for High-speed USB 2.0 connection.
- USB 1.1 devices can't operate at USB 2.0 speeds even when connected to a USB 2.0 hub or host adapter.

■ **Specification:**

Interface	One Upstream Port (USB Mini B type) Four Downstream ports (USB A type)
USB Standards Compliance	Meets USB 2.0 specs
Transmission Speed	Support high speed (480 Mbps) and full speed (12 Mbps) and low speed (1.5 Mbps)
External AC adapter Index	Input: 100-240V~0.5A MAX, 47-63Hz Output: +5V/2.1A 
Operating temperature	0°C to 40°C
Operating humidity	5% to 90% (non-condensing)

■ **Packing List:**

1. The USB 2.0 Hub
2. USB Cable (A type to Mini B type 1.8 M)
3. AC adapter(DC5V, 2.1A)
4. This Manual.